

GSX-S 150

URBAN ROAD LEADER



GSX-S 150

BIKE FEATURES



4-STROKE, DOHC,
4-VALVE, 6-SPEED



Vertically Stacked LED
Headlights



Tail Light and LED License
Plate Light



Tubeless Tires with
10-spoke Cast Wheels



Shutter Key Lock



Sporty Separated Seat
Design



Suzuki Easy Start System



Decent Steering Angle



Aura Yellow / Pearl Brilliant White (ATZ)



Metallic Titan Blue (YSF)

SPECIFICATIONS

ENGINE	Type	Twincam 4 Valve, DOHC, 4 Stroke	
	Cooling System	Liquid Cooled	
	Bore x Stroke	62.0 x 48.8 mm	
	Displacement	147 cc	
	Ignition System	Electronic Transistorized	
	Compression Ratio	11.5 : 1	
	Carburetion	Fuel Injection	
	Starter System	Electric	
	Lubrication System	SJCS (Suzuki Jet Cooling System)	
TRANSMISSION	Clutch System	Wet Sump	
	Transmission	6 Speed Constant Mesh	
CHASSIS	Suspension	Front	Telescopic, Coil Spring, Oil Damped
	Suspension	Rear	Mono Shock with Swingarm (Link Type)
	Brake	Front	Disc Brake
	Brake	Rear	Disc Brake
	Tire Size	Front	90/80-17M/C 46P (Tubeless)
	Tire Size	Rear	130/70-17M/C 62P (Tubeless)
	Wheel Type	Cast Wheel	
	Fuel Tank Capacity	11.0 Liter	
DIMENSIONS	Width x Length x Height	745 x 2,000 x 1,035 mm	
	Wheelbase	1,300 mm	
	Ground Clearance	155 mm	
	Seat Height	785 mm	
	Caster/Trail	26 / 93 mm	
	Full Weight	133 kg	



SUZUKI MALAYSIA SDN. BHD. 202001012115 (1368435-X)

(Exclusive & Sole Importer / Assembler / Distributor for Suzuki Motorcycle, Scooter, ATV, Spare Parts & Accessories)

No.12 & 14, Jalan Jurunilai U1/20, Seksyen U1, Hicom Glenmarie Industrial Park, 40150 Shah Alam, Selangor Darul Ehsan.

Tel: 603-5566 5688 Fax: 603-5566 5699

[f suzukimalaysia](https://www.facebook.com/suzukimalaysia)
[suzukimalaysiasb](https://www.instagram.com/suzukimalaysiasb)
[suzukimalaysia1](https://www.twitter.com/suzukimalaysia1)
www.suzuki.com.my

* Specifications are subject to change without prior notice
** Pictures displayed are for illustration purposes only.
Actual product may vary.

